

MODEL		DB-128	DC 5 Amp		
Power Rating (Watt / A)		60W/5A			
Input AC	AC Voltage Range	220 Vac ± 25%			
	Frequency Rang	50-60 Hz ± 6%			
Output DC	DC Voltage Rang	12.8 Vdc ± 2% (Online-mode)			
		10.5 Vdc - 13.5 Vdc (Backup-Mode)			
System and Protection Mode	Surge Protection	Varistor (1,000,000 W. within 100 Micro-Sec)			
	Overload and Output	Overload and Short Circuit			
	Shot Circuit Protection	With Feedback Current Limiting			
		and Input AC Fuse, Output DC Fuse Protection			
	Low Voltage Battery Protection	Automatic Cut - Off			
LED Display	Online / Charging / Output DC Regulator	Green LED			
	Backup (Battery - On)	Red LED			
	Low battery	Yellow LED			
	Battery Level	Green LED 4 Level			
Battery	TYPE	Sealed Lead Acid Matenance Free			
	Recharge Time	6 - 8 Hours (90% After Fully Discharged)			
	Automatic Charging System	When Online AC			
	Technical	Constan Voltage and limit Current			
Backup	Backup Time (Depends On Load)	CCTV 2 Camera	CCTV 4 Camera	CCTV 6 Camera	CCTV 8 Camera
		>6.30 Hour	>5 Hour	>4 Hour	>3 Hour
Physical	Size W x L x H (Cm.)	24.3 x 29 x 8.7			
	Weight	6 Kg.			