

KEY FEATURES

Model : BalunHD800C

- 1) 5MP HD-CVI/TVI/AHD Passive Video BALUN
- 2) Male BNC with extended pigtail
- 3) NTSC, PAL & SECAM video format compatible
- 4) Real-time transmission
- 5) No power required
- 6) Exceptional interference rejection
- 7) Built-in TVS (Transient Voltage Suppressors) for surge protection
- 8) Lighting protection design Grade: III
- 9) 50 dB crosstalk and noise immunity
- 10) Wave Filter Design, Anti-Static Design
- 11) Compact size and easy installation
- 12) ABS engineering plastic housing



www.karethailand.com

Specification		
Model		HD800C
Product Name		HD Single Channel Passive Video BALUN
Applied Devices		CCTV cameras, monitors, DVR and other CCTV equipment
Properties	Transmission Signal	PAL, NTSC, SECAM
	Max. Distance	AHD/CVI: 400M (Max.) TVI: 200M (Max.)
	Category Type	UTP CAT5/5e/6
Video Transmission Properties and Port	Coaxial Video Connector	BNC-M
	Twisted-pair video connector	Push-terminal
	Compatible Format	AHD/TVI/CVI/CVBS
	Resolution	720P/960P/1080P/3MP/4MP/5MP
	Anti-interference	>60dB
Protection	ESD	1a contact discharge electricity level 3 1b air discharge electricity level 3 Per: IEC61000-4-2
	Coaxial Cable Connector	2KV(common-code) Per: IEC1000-4-5
	UTP Cable Connector	2KV(different-code), 4KV(common-code), Per: IEC1000-4-5
Impedance	BNC Connector	75 Ohms
	UTP Cable	100 Ohms
	MTBF	>10000H
Mechanical	Housing	ABS engineering plastic
	Body Color	Black
	Net Weight	60g
Environmental	Operating Temperature	10° ~ 55° C
	Relative Humidity	0~95% (non-condensing)
	Storage Temperature	-20° ~ 70° C