

KEY FEATURES

PRODUCT : C2006HDM5

- 1) Include 2.8mm lens
- 2) 36pcs Φ5mm LED, IR distance 25-30M
- 3) With cable shield 3-Axis bracket
- 4) Effective pixels: 2592(H)*1944(V)
- 5) OSD or UTC control optional, 4in1 AHD/CVI/TVI/CVBS can be adjusted by Up/Down/left/right button on OSD cable or on DVR's coaxial control menu, can adjust image & functions freely
- 6) Transmitting distance up to 500M



5.0 Mega Pixel HD Camera with 30M IR and Fixed Lens

SPECIFICATION

Camera	
Image Sensor	1/2.9" SONY 6.8MP Starvis Exmor CMOS IMX326+FH8538M
Image Resolution	5.0MP/4.0MP
Effective Pixels	5.0MP: 2592(H)*1944(V); 4.0MP: 2688(H)*1520(V)
Frame Rate	5.0MP@20fps/5.0MP@12.5fps/4.0MP@25fps/4.0MP@30fps/4MP@15fps/1080P@25fps/1080P@30fps
TV System	PAL/NTSC
Video Out	AHD: 5.0MP/4.0MP, can be 4.0MP 15fps; TVI: 5.0MP/4.0MP; CVI: 4MP; CVBS
Auto	Auto
S/N Ratio	≥50dB
Scanning System	Progressive Scan
Lens	
Focus Length	2.8mm
Night Vision	
Infrared LED	Φ5 x 36PCS
Infrared Distance	25-30M
IR Power On	CDS Auto Control
Camera Features	
Starlight	/
Day/Night	EXT(Default)/AUTO/COLOR/B/W
OSD Menu Language	CHN/ENG
White Balance	AUTO / MANUAL
Picture Adjustment	Contrast/Sharpness/COLOR GAIN/DNR/Format/DWDR
OSD	Optional
UTC	Optional
Dip Switch	/
General	
Housing	Metal, IP66
Bracket	YES
Dual Voltage	NO
Heater & Fan	NO
Audio	/
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	200(L) x 63(H) x 63(D)mm
Weight	400g
Package	50pcs/CTN CTN size: 53*52*42CM CTN weight: 22.0kg