

KEY FEATURES

PRODUCT : C284HDM2N

- 1) Include 3.6mm lens
- 2) 36pcs Φ 5mm LED, IR distance 30M
- 3) With cable shield 3-Axis bracket
- 4) Effective pixels: 1920*1080
- 5) OSD or UTC control optional, 4in1 AHD/CVI/TVI/CVBS can be adjusted by Up/Down/left/right button on OSD cable or on DVR's coaxial control menu, can adjust image & functions freely
- 6) Transmitting distance up to 500M



SPECIFICATION

Image Sensor	1/2.7" CMOS, AR0237
DSP	V30E(FH8536E)
Image Resolution	P: 25fps@1920(H)*1080(V) N: 30fps@1920(H)*1080(V)
Minimum Illumination	Color: 0.01Lux @ (F1.2,AGC ON),0 Lux with IR B&W: 0.001Lux@ (F1.2, AGC ON), 0Lux with IR
Electric Shutter	1/25s~1/50,000s, 1/30s~1/60,000s
TV System	PAL/NTSC
Sync System	Internal
S/N Ratio	\geq 50dB
Video Output	AHD/TVI/CVI/CVBS (960H) (BNC)
Lens	3.6mm lens
IR Distance	36pcs Φ 5mm LED, IR distance 30M
IR Power On	No
D&N Mode	Color / B&W
OSD	Support
OSD Menu Language	EN, CN
DNR	3D NR
Picture Adjustment	Yes
White Balance	Auto/Manual
Gain Control	Auto
Vandal-proof Housing	Metal
Power Input	DC12V \pm 10%
Operation Temperature	Temperature -10°C~+50°C, Humidity less than 95%RH
Storage Temperature	Temperature -20°C~+60°C, Humidity less than 95%RH
Dimension	150mm(L) * 82mm(W) * 75.1mm (H), not including size of bracket 201mm(L) * 82mm(W) * 75.1mm (H), including size of bracket
Weight	550g
Package	50pcs/CTN CTN size: 53*52*41CM CTN weight: 21.7kg