

# Model: C284HDM2V



**HD**  
**1080p**

**STARVIS**

## C284HDM2V

- 1) Include 3.6mm lens
- 2) 36pcs 5mm LED, IR distance 30M
- 3) With cable shield 3-Axis bracket
- 4) Effective pixels: 1920\*1080
- 5) UTC control in default, OSD cable control optional, 4in1 AHD/CVI/TVI/CVBS can be adjusted by Up/Down/left/right button on OSD cable or on DVR's coaxial control menu, can adjust image & functions freely
- 6) Transmitting distance up to 500M



## 2.0 Mega Pixel HD Camera with 30M IR and Fixed Lens

### Specification

Model	1/2.8" CMOS, SONY IMX307
Image Sensor	NVP244IH
DSP	P: 25fps@1920(H)*1080(V) N: 30fps@1920(H)*1080(V)
Image Resolution	Color: 0a.00ILux @ (F1.2,AGC ON), 0 Lux with IR B&W: 0.000ILux@ (F1.2, AGC ON), 0Lux with IR
N: 30fps@1920(H)*1080(V)	1/25s-1/50,000s, 1/30s-1/60,000s
Minimum Illumination	PAL/NTSC
B&W: 0.000ILux@ (F1.2, AGC ON), 0Lux with IR	Internal
Electric Shutter	≥50dB
TV System	AHD/TVI/CVI/CVBS (960H) (BNC)
Sync System	3.6mm lens
S/N Ratio	36pcs Φ5mm LED, IR distance 30M
Video Output	No
Lens	Color / B&W
IR Distance	Support
IR Power On	EN, CN
D&N Mode	3D NR
OSD	Yes
OSD Menu Language	Auto/Manual
DNR	Auto
Picture Adjustment	Metal
White Balance	DC12V±10%
Gain Control	Temperature -10°C~+50°C, Humidity less than 95%RH
Vandal-proof Housing	Temperature -20°C~+60°C, Humidity less than 95%RH
Power Input	150mm(L) * 82mm(W) * 75.1mm (H), not including size of bracket 201mm(L) * 82mm(W) * 75.1mm (H), including size of bracket