

KEY FEATURES

PRODUCT : C284HDM5

- 1) Include 3.6mm lens
- 2) 36pcs Φ 5mm LED, IR distance 30M with IR cut
- 3) With cable shield 3-Axis bracket
- 4) Effective pixels: 2560*1944
- 5) OSD or UTC control optional, 4in1 AHD/CVI/TVI/CVBS can be adjusted by Up/Down/left/right button on OSD cable or on DVR's coaxial control menu, can adjust image
- 6) Transmitting distance up to 500M
- 7) Standard IP66



SPECIFICATION

Image Sensor	1/2.9" CMOS, SONY IMX326
DSP	V30E(FH8536E)
Image Resolution	2560(H)*1944(V) 5.0MP 4:3 2560(H)*1440(V) 4.0MP 16:9
Minimum Illumination	Color: 0.1Lux @ (F1.2,AGC ON),0 Lux with IR B&W: 0.01Lux@ (F1.2, AGC ON), 0Lux with IR
Electric Shutter	Auto
TV System	PAL/NTSC
Sync System	Internal
S/N Ratio	\geq 50dB
Video Output	AHD: 5.0MP/4.0MP TVI: 5.0MP/4.0MP CVI: 4.0MP CVBS
Lens	3.6mm lens
IR Distance	36pcs Φ 5mm LED, IR distance 30M with IR cut
IR Power On	Auto
D&N Mode	Color / B&W
OSD	Support
OSD Menu Language	EN, CN
DNR	3D NR
Picture Adjustment	Yes
White Balance	Auto/Manual
Gain Control	Auto
Vandal-proof Housing	Metal/IP66
Power Input	DC12V \pm 10%
Operation Temperature	Temperature -10°C~+50°C, Humidity less than 95%RH
Storage Temperature	Temperature -20°C~+60°C, Humidity less than 95%RH
Dimension	73.5mm(L) * 73mm(W) * 76mm (H), not including size of bracket 158mm(L) * 73mm(W) * 76mm (H), including size of bracket
Weight	550g