

KEY FEATURES

Model : C299HDM5

- 1) 3.6mm lens
- 2) 36pcs Φ 5mm LED, IR distance 30M
- 3) With cable shield 3-Axis bracket
- 4) Support UTC control, OSD optional, 4in1 AHD / CVI / TVI / CVBS
can be adjusted by Up / Down / left / right button on
OSD cable or on DVR's coaxial control menu,
can adjust image & functions freely
- 5) Transmitting distance up to 500M



Specification

Specification	
Model	C290HDM5
Image Sensor	1/2.9" CMOS, SONY
Image Resolution	2560(H)*1944(V), 5.0M pixels, 4:3 2560(H)*1440(V), 4.0M pixels, 16:9
Minimum Illumination	Color: 0.1Lux @ (F1.2,AGC ON),0 Lux with IR B&W: 0.01Lux@ (F1.2, AGC ON), 0Lux with IR
Electric Shutter	Auto
TV System	PAL/NTSC
Sync System	Internal
S/N Ratio	\geq 50dB
Video Output	AHD: 5MP@20fps/4MP@25fps / 4MP@30fps TVI: 5MP@20fps/4MP@25fps / 4MP@30fps CVI: 4MP@25fps / 4MP@30fps CVBS
Lens	3.6mm lens
IR Distance	36pcs Φ 5mm LED, IR distance 30M
IR Power On	Auto
D&N Mode	Color / B&W
OSD	Support
OSD Menu Language	EN, CN
DNR	3D NR
Picture Adjustment	Yes
White Balance	Auto/Manual
Gain Control	Auto
Vandal-proof Housing	Metal
Power Input	DC12V \pm 10%
Operation Temperature	Temperature -10°C~+50°C, Humidity less than 95%RH
Storage Temperature	Temperature -20°C~+60°C, Humidity less than 95%RH
Dimension	302(L) * 96(W) * 71(H)mm
Weight	690g