

## KEY FEATURES

## PRODUCT : C531HDM2E

- 1) Include Mega pixel 1.44mm fisheye lens, with IR-Cut
- 2) 27pcs Φ5mm LED, IR distance: 20m
- 3) Plastic Housing
- 4) Effective pixels: 1920\*1080
- 5) OSD menu, 4in1 AHD/CVI/TVI/CVBS can be adjusted by Up/Down/left/right OSD button, can adjust image & functions freely
- 6) Transmitting distance up to 500M



## SPECIFICATION

Image Sensor	1/2.9" SONY IMX323
DSP	V30E (FH8536E)
Effective Pixel	PAL/NTSC: 1920(H) * 1080(V)
Minimum Illumination	Color:0.01Lux, F1.2
Image Resolution	AHD/TVI/CVI: 2.0MP, 1080P, CVBS: 2000TVL
Electric Shutter	AUTO/MANUAL(1/50\60 ~ 1/100,000 sec)
TV System	PAL/NTSC
Sync System	Internal
S/N Ratio	>46dB
Video Output	AHD/TVI/CVI/CVBS (BNC), AHD in default
Lens	1.44mm Fisheye lens
IR Distance	27pcs Φ5mm LED, IR distance 20M
WDR	Yes
D&N Mode	Auto/Color/B&W/EXTERN
OSD	Support
OSD Menu Language	EN, CN
DNR	Off/Low/Middle/High
Picture Adjustment	Yes
White Balance	Auto/Manual
Gain Control	Auto
Waterproof Housing	Yes
Power Input	DC12V±10%, 500mA
Operation Temperature	Temperature -10°C~+50°C, Humidity less than 95%RH
Storage Temperature	Temperature -20°C~+60°C, Humidity less than 95%RH
Dimension	190mm(D)
Weight	500g
Package	28pcs/CTN
	CTN size: 64mm*55mm*46mm
	CTN weight: 15kg