

## Outdoor Mini dome camera

PRODUCT MODEL No. S13110S

### KEY FEATURES

Adopt 10x 1/3" SONY CCD

Rotate 360° in horizontal direction, driven by exact engine, operate stably with Precise position-setting.

The rotation speed can be adjustable according to the zoom rate of camera lens, auto-focus, auto white balance.

Built-in OSD. Several control protocols are compatible and

Baud rate is adjustable;

Vertical 90° continuous monitoring after auto reversing 180°



Normal light monitoring results



Infrared lamp open monitoring results

### DIMENSIONS



### SPECIFICATIONS

Image sensor	1/3" Sony CCD
Signal model	PAL/NTSC
Horizontal resolution	700TVL
Effective pixel	976 (Horizontal) x 596 (Vertical)
Minimum illumination	Color to B/W, Color: 0.01Lux, B/W: 0.001Lux
S/N radio	>60dB(Enhanced)
Backlight compensation	On/Off
White balance	Auto
Electronic shutter	1/50 ~ 1/12000 seconds
Focus length	5 ~ 50mm
Optical focus	10X
Focus	Auto/manual, take high-performance DSP to realize complete digit and ultra-high speed focus function
Presets	256
Patrol track	4groups, each can record 200 actions
Cruise track	Total 30 presets can join cruise, can setting the presets' residence time
Other scan	Support Horizontal scan, deuce area scan, scan random
Rotation range	Horizontal 360° unlimited rotation, Vertical 90° ,auto reversal
Rotation speed	Horizontal & Vertical Min 0.01° ,Max 200° /S
Communications	RS-485, PELCO D, PELCO P
OSD	Yes
Temperature control	built-in
IR distance	80m
Power supply	DC12V/2A
Material	Aluminum shell,waterproof Criterion IP66
Work environment	-20°C ~ +50°C(select temperature control accessories), <95%RH



White Balance



WDR Wide Dynamic Range



Masking



DNR Digital Noise Reduction



Strong inhibition

