




## KEY FEATURES

## PRODUCT : D3054HH

- ◆ Super Strong processing capacity: can realize 4CH AHD 1080P@15FPS recording/4CH AHD 720P realtime recording and 4CH AHD 1080P@15FPS playback /4CH AHD 720P realtime playback synchronously.
- ◆ Powerful net service (support DHCP, PPPOE, FTP, DNS, DDNS, ARSP(www.dvrcenter.com) , NTP, UPNP, EMAIL, IP authority, IP search, alarm center, etc) , complete enclosure (WEB, CMS, SDK) , to easily achieve interconnection.
- ◆ Support 3G & WIFI extension.
- ◆ Support kinds of mobile and web monitor.
- ◆ Multiplex operation : Preview , recording, playback, backup, network live, mobile phone view ; all operations are independent of each other.
- ◆ Support many recording modes: Auto-continuing recording, timing recording, motion detection recording.



## SPECIFICATION

|                            |   |
|----------------------------|---|
| Operation interface        | 16 bit real color GUI interface support mouse operation   |
| Display screen             | 1/4 screen  |
| Image encode               | H.264   |
| Monitor quality            | VGA: 1080P; HDMI: 1080P   |
| Playback quality           | Max support 1080P under HVR and NVR mode; Max support AHD 1080P under DVR mode;                                     |
| Encode capability          | 4CH AHD 1080P@15FPS/4CH AHD 720P real time(DVR mode)  |
| Decode capability          | 4CH AHD 1080P@15FPS/4CH AHD 720P real time(DVR mode)  |
| Multi-mode video input     | DVR mode :4CH*1080P/4CH *720P   |
|                            | HVR mode:2 CH*1080P (analog) +2CH*1080P(network)/4CH*720P +4CH*720P   |
|                            | NVR mode:4CH*1080P/1CH*1080P+8CH*720P/20CH*960H   |
| Motion detection           | Each channel can set 192 (16*12) detection area; can set multi-level of flexibility (for local analog channel only) |
| Audio compression          | G.711A  |
| Record mode                | Manual, alarm, motion detection, timing   |
| Local playback             | 1-4ch playback synchronously; Under the mode of DVR, Max support 4CH AHD 1080P playback synchronously               |
| Video search               | Time, date, event, channel search   |
| Space occupation           | Video: 1080P 20~30G/day*channel, 720P 20G/day*channel; 960H 12~20G/day*channel                                      |
|                            | audio: 691.2M/day*channel   |
| Video storage              | Local HDD、Network   |
| Back up mode               | Network backup、USB portable HDD、USB DVD-RW  |
| Video input / Video output | 4CH BNC / 1CH VGA, 1CH HDMI   |
| Audio input / Audio output | 4CH RCA / 1CH RCA   |
| Alarm input / Alarm output | 2CH / 1CH   |
| Network port               | RJ45 10M/100M self-adaptive Ethernet port   |
| PTZ control                | 1 RS485; support multi kinds of PTZ Protocol  |
| USB port                   | 2*USB2.0  |
| HDD port                   | 2 SATA (each max support 4TB)   |
| Wireless port              | 3G、WIFI(extension via USB port)   |
| Tour                       | Yes   |
| Remote controller          | Yes   |
| Power                      | 12V/4A  |
| Dimension                  | 325(Length) x 230(Width) x 52(Height)   |