

KEY FEATURES

PRODUCT : D8126HPT



SPECIFICATION

System	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
	Operation interface	16bit real color GUI interface support mouse operation
Interface	Display screen	1/4/8/9/16 screen
	Video standard	PAL(625 lines, 50fps); NTSC(525 lines, 60fps)
Video	Image encode	H.264(High Profile)
	Monitor quality	Monitor: 1080P, 720P, D1; VGA, HDMI
	Playback quality	1080P/D1/HD1/CIF
	Encode capability	16ch 1080P(12FPS)
	Decode capability	16*1080P (12FPS)
	Multi-mode video input	AHD: 16*1080P (12FPS) AHD; 16*720P AHD
		HVR: 8*1080P AHD+8*1080P IP
		NVR: 8*1080P+8*960P; 8*3M; 4*5M
Audio	Motion detection	192(16×12) detection areas, multiple sensitivity
	Audio compression	G711A
	Bidirectional talk	support
Record and playback	Record mode	manual>alarm>motion detection>timing
	Local playback	16ch playback synchronously
	Video search	Time, date, event, channel search
Storage and back up	Space occupation	Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; 960H 12~20G/day*channel; 720P 24~30G/day*channel
		Audio: 691.2M/day*channel
	Video storage	Local HDD, Network
	Back up mode	Network backup, USB portable HDD, USB imprint, SATA imprint
	Video input / output	16ch CVBS/BNC(1.0Vp-p,75Ω) / 1ch VGA, 1ch HDMI
	Audio input / output	2ch RCA(200-2800mV,30KΩ) / 1ch RCA(200-3000mV,5KΩ)
	Alarm input / output	no, 4ch optional / no, 1ch optional
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	1*RS485
	USB port	2*USB2.0
	HDD port	2 SATA ports(each max to 6T)
	Wireless port	3G, WIFI(extension via USB port)
Other	Power	12V/4A
	Consumption	<10W(not including HDD)
	Temperature	0° C~ +55° C~
	Humidity	10%—90%
	Atmosphere pressure	86kpa—106kpa
	Dimension	L325*W250*H52MM
	Weight	2.5kg