

KEY FEATURES

PRODUCT : D8204KL

4CH 5M 6in1 AHD/XVI/TVI/CVI/CVBS/IP DVR
 4CH 5M (11FPS/CH), 4CH 4M (15FPS/CH), 4CH 3M (18FPS/CH)
 4CH 2M (Real-time), Recording
 4CH 5M (11FPS/CH) Playback
 4CH video input, 4CH audio input
 1CH audio output, No alarm, with RS485
 Support VGA and HDMI simultaneously output
 Support 2pcs of HDD, Max. 6TB each



SPECIFICATION

System	Main processor	Technical grade embedded microprocessor Hi3521A
	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
Interface	Operation interface	16bit real color GUI interface support mouse operation
	Display screen	1/4 screen
Video	Video standard	PAL(625 lines, 50fps); NTSC(525 lines, 60fps)
	Image encode	H.264 (High Profile) and H.264+
	Monitor quality	Monitor: 720P, D1; VGA, HDMI
	Playback quality	5M
	Encode capability	4ch 5M (11fps)
	Decode capability	4ch 5M (11fps), 4ch 4M (15fps); 4ch 3M (18fps), 4ch 2M (real-time)
	Multi-mode video input	AHD: 4*5M(11fps); 4*4M (15fps); 4*3M (18fps) AHD/XVI/TVI/CVI/CVBS: 4*1080P HVR: 2*5M (AHD)+2*5M (IP) NVR: 8*1080P+8*960P; 4*3M; 4*5M
Motion detection	192(16×12) detection areas, multiple sensitivity	
Audio	Audio compression	G711A
	Bidirectional talk	support
Record and playback	Record mode	manual>alarm>motion detection>timing
	Local playback	4ch playback synchronously
	Video search	Time, date, event, channel search
Storage and back up	Space occupation	Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; 960H 12~20G/day*channel; 720P ~20G/day*channel; 1080P 20~30G Audio: 691.2M/day*channel
	Video storage	Local HDD, Network
	Back up mode	Network backup, USB portable HDD, USB imprint, SATA imprint
Interface	Video input	4ch CVBS/BNC(1.0Vp-p,75Ω)
	Video output	1ch VGA, 1ch HDMI
	Loop output	No
	Audio input	4ch RCA(200-2800mV,30KΩ)
	Audio input	1ch RCA(200-3000mV,5KΩ)
	Alarm input	No
	Alarm output	No
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	1*RS485
	USB port	2*USB2.0
	HDD port	2 SATA ports(each max to 4T)
	Wireless port	3G, WIFI(extension via USB port)
Other	Power	12V/4A
	Consumption	<15W(not including HDD)
	Temperature	0° C~ +55° C~
	Humidity	10%—90%
	Atmosphere pressure	86kpa—106kpa
	Dimension	L325*W250*H52MM
	Weight	2.5kg