

KEY FEATURES

PRODUCT : D8208HP



SPECIFICATION

System	Operating system	Embedded LINUX operating system	
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.	
	Operation interface	16bit real color GUI interface support mouse operation	
Interface	Display screen	1/4/8/ screen	
	Video standard	PAL(625 lines, 50fps); NTSC(525 lines, 60fps)	
Video	Image encode	H.264(High Profile)	
	Monitor quality	Monitor: 1080P, 720P, D1; VGA, HDMI	
	Playback quality	1080P/D1/HD1/CIF	
	Encode capability	8ch 1080P(12FPS)	
	Decode capability	4*1080P (12FPS)	
	Multi-mode video input	AHD: 8*1080P(12FPS) AHD; 8*720P AHD	
		HVR: 1*1080P AHD+1*1080P IP; 4*720P(AHD)+4*720P(IP)	
NVR: 2*1080P+2*720P; 8*720P			
Motion detection	192(16×12) detection areas, multiple sensitivity		
Audio	Record mode	manual>alarm>motion detection>timing	
Record and playback	Local playback	4ch playback synchronously	
	Video search	Time, date, event, channel search	
Storage and back up	Space occupation	Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; 960H 12~20G/day*channel; 720P 24~30G/day*channel	
		Audio: 691.2M/day*channel	
	Video storage	Local HDD, Network	
	Back up mode	Network backup, USB portable HDD, USB imprint, SATA imprint	
Other	Video input / output	8ch CVBS/BNC(1.0Vp-p,75Ω) / 1ch VGA, 1ch HDMI	
	Audio input	2ch RCA(200-2800mV,30KΩ) / 1ch RCA(200-3000mV,5KΩ)	
	Alarm input / output	Optional / Optional	
	Network port	RJ45 10M/100M self-adaptive Ethernet port	
	PTZ control	1*RS485	
	USB port	2*USB2.0	
	HDD port	2 SATA ports(each max to 6T)	
	Wireless port	3G, WIFI(extension via USB port)	
	Power	12V/4A	
	Consumption	<10W(not including HDD)	
	Temperature	0° C~ +55° C~	
Humidity	10%—90%		
Atmosphere pressure	86kpa—106kpa		
Dimension	L325*W250*H52MM		
Weight	2.5kg		