

## KEY FEATURES

## PRODUCT : D8208KL

8CH 5M 6in1 AHD/XVI/TVI/CVI/CVBS/IP DVR  
 8CH 5M (11FPS/CH), 8CH 4M (15FPS/CH)  
 8CH 3M (18FPS/CH), 8CH 2M (Real-time) recording  
 4CH 5M (11FPS/CH) Playback  
 8CH video input, 4CH audio input,  
 1CH audio output, No alarm, with RS485  
 Support VGA and HDMI simultaneously output  
 Support 2pcs of HDD, Max. 6TB each  
 Support USB 3G & WiFi



## SPECIFICATION

System	Main processor	Technical grade embedded microprocessor Hi3531A
	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
Interface	Operation interface	16bit real color GUI interface support mouse operation
	Display screen	1/4/8/9 screen
Video	Video standard	PAL(625 lines, 50fps); NTSC(525 lines, 60fps)
	Image encode	H.264 (High Profile) and H.264+
	Monitor quality	Monitor: 4M, 3M, 720P, D1; VGA, HDMI
	Playback quality	5M
	Encode capability	8ch 5M (11FPS/CH), 8CH 4M (15FPS/CH), 8CH 3M (18FPS/CH), 8CH 2M (Real-time)
	Decode capability	4ch 5M (11FPS/CH)
	Multi-mode video input	AHD: 8*5M(11fps); 8*4M (15fps); 8*3M (18fps) AHD/XVI/TVI/CVI/CVBS: 8*1080P HVR: 4*5M (AHD)+4*5M (IP) NVR: 8*3M; 4*5M
Motion detection	192(16×12) detection areas, multiple sensitivity	
Audio	Audio compression	G711A
	Bidirectional talk	support
Record and playback	Record mode	manual>alarm>motion detection>timing
	Local playback	4ch playback synchronously
	Video search	Time, date, event, channel search
Storage and back up	Space occupation	Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; 960H 12~20G/day*channel; 720P 24~30G/day*channel Audio: 691.2M/day*channel
	Video storage	Local HDD, Network
	Back up mode	Network backup, USB portable HDD, USB imprint, SATA imprint
Interface	Video input	8ch CVBS/BNC(1.0Vp-p,75Ω)
	Video output	1ch VGA, 1ch HDMI
	Loop output	No
	Audio input	4ch RCA(200-2800mV,30KΩ)
	Audio input	1ch RCA(200-3000mV,5KΩ)
	Alarm input	No
	Alarm output	No
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	1*RS485
	USB port	2*USB2.0
	HDD port	2 SATA ports(each max to 6T)
Wireless port	3G, WIFI(extension via USB port)	
Other	Power	12V/4A
	Consumption	<15W(not including HDD)
	Temperature	0° C~ +55° C~
	Humidity	10%—90%
	Atmosphere pressure	86kpa—106kpa
	Dimension	L325*W250*H52MM
	Weight	2.5kg