

KEY FEATURES

PRODUCT : D8608KL-5

- 8CH 8M 6in1 AHD/XVI/TVI/CVI/CVBS/IP DVR
- 8CH 8M (8FPS/CH) recording & 8CH 8M (8FPS/CH) Playback
- 8CH video input, 4CH audio input, 1CH audio output, No alarm, No RS485
- Support VGA and HDMI simultaneously output
- Support 2pcs of HDD, Max. 8TB each
- Support USB 3G & WiFi



SPECIFICATION

System	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
Interface	Operation interface	16bit real color GUI interface support mouse operation
	Display screen	1/4/8/9 screen
Video	Video standard	PAL(625 lines, 50fps); NTSC(525 lines, 60fps)
	Image encode	H.265/H.265+ (High Profile)
	Monitor quality	Monitor: 8M; 5M; 4M, 3M, 1080P; 720P, D1; VGA, HDMI
	Preview Mode	XVI/AHD: 8*8M (15fps); 6in1: 8*5M (20fps); 8*4M real time
	Encode capability	XVI/AHD: 8*8M (8fps); 6in1: 8*5M (14fps); 8*4M (18fps); 8*3M (21fps); 8*1080P real time
	Decode capability	XVI/AHD: 8*8M (8fps); 6in1: 8*5M (14fps); 8*4M (18fps); 8*3M (21fps); 8*1080P real time
	Multi-mode video input	XVI/AHD: 8*8M (8fps); 6in1: 8*5M (14fps); 8*4M (18fps); 8*3M (21fps); 8*1080P real time
	Motion detection	192(16*12) detection areas, multiple sensitivity
Audio	Audio compression	G711A
	Bidirectional talk	support
Record and playback	Record mode	manual>alarm>motion detection>timing
	Local playback	4ch playback synchronously
	Video search	Time, date, event, channel search
Storage and back up	Space occupation	Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; 960H 12~20G/day*channel; 720P 24~30G/day*channel Audio: 691.2M/day*channel
	Video storage	Local HDD, Network
	Back up mode	Network backup, USB portable HDD, USB imprint, SATA imprint
Interface	Video input	8ch CVBS/BNC(1.0Vp-p,75Ω)
	Video output	1ch VGA, 1ch HDMI
	Loop output	No
	Audio input	4ch RCA(200-2800mV,30KΩ)
	Audio output	1ch RCA(200-3000mV,5KΩ)
	Alarm input	No
	Alarm output	No
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	No RS485
	USB port	2*USB2.0
	HDD port	2 SATA ports(each max to 8T)
	Wireless port	3G, WIFI(extension via USB port)
	Other	Power
Consumption		<15W(not including HDD)
Temperature		0° C~ +55° C~
Humidity		10%—90%
Atmosphere pressure		86kpa—106kpa
Dimension		L325*W250*H52MM
	Weight	2.5kg