

KEY FEATURES

PRODUCT : D8704KR-5

- 4CH 5M 6in1 AHD/XVI/TVI/CVI/CVBS/IP DVR
- 4CH 5M (6FPS/CH) recording & 1CH 5M (6FPS/CH) Playback
- 4CH video input, 1CH audio input, 1CH audio output, No alarm, No RS485
- Support VGA and HDMI simultaneously output
- Support 2pcs of HDD, Max. 8TB each
- Support USB 3G & WiFi



SPECIFICATION

System	Main processor	Technical grade embedded microprocessor Hi3520DV400
	Operating system	Embedded LINUX operating system
	System resource	Multi-channel real-time recording synchronously, multi-channel real-time playback, multi-channel multi-user network operation, USB back up.
Interface	Operation interface	16bit real color GUI interface support mouse operation
	Display screen	1/4 screen
Video	Video standard	PAL (625 lines, 50fps); NTSC (525 lines, 60fps)
	Image encode	H.265+
	Monitor quality	VGA, HDMI
	Preview Mode	4*5M@12fps/4*4M@15fps/4*3M@18fps/4*1080P
	Encode capability	4*5M@6fps/4*4M@8fps/4*3M@10fps/4*1080P
	Decode capability	1*5M@6fps/4*4M@8fps/4*3M@10fps/4*1080P
	Multi-mode video input	XVI/AHD/TVI/CVI/CVBS: 4*5M (6fps); 4*4M (8fps) HVR: 2*4M Analog+2*4M IP NVR: 16*1080P; 9*1080P; 16*960P; 4*5M
Audio	Motion detection	192(16x12) detection areas, multiple sensitivity
	Audio compression	G711A
Record and playback	Bidirectional talk	support
	Record mode	manual>alarm>motion detection>timing
	Local playback	4ch playback synchronously
Storage and back up	Video search	Time, date, event, channel search
	Space occupation	Video: CIF 4~5G/day*channel, D1 16~20G/day*channel; 960H 12~20G/day*channel; 720P ~20G/day*channel; 1080P 20~30G Audio: 691.2M/day*channel
	Video storage	Local HDD, Network
	Back up mode	Network backup, USB portable HDD, USB imprint, SATA imprint
Interface	Video input	4ch CVBS/BNC(1.0Vp-p,75Ω)
	Video output	1ch VGA, 1ch HDMI
	Loop output	No
	Audio input	1ch RCA (200-2800mV,30KΩ)
	Audio output	1ch RCA (200-3000mV,5KΩ)
	Alarm input	No
	Alarm output	No
	Network port	RJ45 10M/100M self-adaptive Ethernet port
	PTZ control	No
	USB port	2*USB2.0
	HDD port	2 SATA ports (each max to 8T)
	Wireless port	3G, WIFI (extension via USB port)
Other	Power	12V/4A
	Consumption	<15W(not including HDD)
	Temperature	0° C~ +55° C~
	Humidity	10%—90%
	Atmosphere pressure	86kpa—106kpa
	Dimension	L325*W250*H52MM
Weight	2.5kg	