


## เครื่องบันทึกภาพ ระบบไอพี (NVR) NETWORK VIDEO RECORDER

NVR 4 CH : N7104NQ



### DIMENSION



### SPECIFICATIONS

Models		N7104NQ
System	User Interface	Graphic User interface(OSD Menu)
	OS	Embedded Linux
	ONVIF	Support
	Security	Administrator; Different authority for users
Video	Video input	4 CH 1080P IPC (by switch)
	Video output	CVBS/VGA/HDMI
	Display	1/4 optional
	VGA	1024*768,1280*1024,1440*900,1366*768,720P,1080P
	Video encoding resolution	PAL:720P(1280X720); 1080P(1920*1080) / NTSC:720P(1280X720); 1080P(1920*1080)
	Video frame rate	PAL: 1-25FPS NTSC:1-30FPS
Audio	Audio compress	ADPCM
	Audio in	IPC with audio
	Audio out	1 out BNC
Image & Storage	Video compress	H.264
	Image quality	720P/1080P
	Sub stream	Sub stream1:VGA/QVGA; Sub stream2:540P
	Resolution	4CH 1080P recording & 1CH realtime playback/4CH Playback(15FPS) 4CH 720P recording & 4CH realtime playback;
	Video Bit Rate	720P:1536kbps-3072kbps;1080P:2048-8192kbps
	Audio Bit Rate	8—32Kbps
	Storage	1 HDD
Alarm	Alarm in/out	NO
Others	Recording	Manual/alarm/motion detection/timing
	Network	RJ45 1000MB Protocol: TCP/IP, PPPOE, SMTP,UPNP,DHCP,DDNS,RTSP
	Voice talk	Support
	Control Method	Remote control, USB mouse, panel control
	Mobile live view	I phone //IPAD/Android/Blackberry
	Domain name server	Support 88110,reelink,3322, dyndns, no-ip, changeip, dnsexit domain name server as default value.
	Backup	USB2.0, Network
Power Supply	NVR	DC 12V 2A
	IPC	individual power supply(DC 12V 2A)
Working Environment		Working temperature: -10°C~+60°C; Working humid:10%~ 90%
Device Dimension		1HDD case:230mm (W)×315mm (D)×40mm (H)
Weight		1HDD Case:≤1.5KG;