

Model: C345HDM5E

- 1) Include 2.8mm lens
- 2) 24pcs Φ 5mm LED, IR distance 20M
- 3) Vandal-proof Dome Camera
- 4) Effective pixels: 2592(H)*1944(V)
- 5) OSD or UTC control optional, 4in1 AHD/CVI/TVI/CVBS can be adjusted by Up/Down/left/right button on OSD cable or on DVR's coaxial control menu, can adjust image & functions freely
- 6) Transmitting distance up to 500M



Specification	
Image Sensor	1/2.8" SONY 5.14MP Starvis Exmor CMOS IMX335
Image Resolution	5.0MP/4.0MP
Effective Pixels	5.0MP: 2592(H)*1944(V); 4.0MP: 2688(H)*1520(V)
Frame Rate	5.0MP@20fps/5.0MP@12.5fps/4.0MP@25fps/4.0MP@30fps/4MP@15fps/1080P@25fps/1080P@30fps
TV System	PAL/NTSC
Video Out	AHD: 5.0MP/4.0MP, can be 4.0MP 15fps; TVI: 5.0MP/4.0MP; CVI: 4MP; CVBS
Electronic Shutter	Auto
S/N Ratio	\geq 50dB
Scanning System	Progressive Scan
Focus Length	2.8mm
Infrared LED	Φ 5 x 24PCS
Infrared Distance	20M
IR Power On	CDS Auto Control
Starlight	/
Day/Night	EXT(Default)/AUTO/COLOR/B/W
OSD Menu Language	CHN/ENG
White Balance	AUTO / MANUAL
Picture Adjustment	Contrast/Sharpness/COLOR GAIN/DNR/Format/DWDR
OSD	Optional
UTC	Optional
Dip Switch	/
Housing	Metal
Bracket	NO
Dual Voltage	NO
Heater & Fan	NO
Audio	/
Operation Temperature	(-10 ~ +50 RH95% Max)
Storage Temperature	(-20 ~ +60 RH95% Max)
Power Source	DC12V \pm 10%, 550mA
Dimension	105.5(D) x 72(H) mm
Weight	300g