

**Features**

- 1)Configure device through wired/wireless network
- 2)1/2.9" progressive CMOS sensor
- 3)Support Android/iOS view/Windows PC client remote view
- 4)3.6mm lens
- 5)Day/Night: IR-cut auto switch Filter
- 6)2.0MP/1080P resolution
- 7)Support Onvif
- 8)Dual Light: 2pcs IR LEDs+2pcs White LEDs
- 9)Fast configuration: acoustic smart link configuration (WiFi fast configuration)
- 10)Support TF card, Max. 128GB
- 11)Support human detection and motion detection
- 12)Support two-way audio



WiFi Camera Specification	
<b>Camera</b>	
Image Sensor	1/2.9" CMOS (XM530+SC2235E)
Resolution	2.0MP 1080P
Video Compression Format	H.265
Frame Rate	25fps (PAL/NTSC)
Electric Shutter	Auto
Minimum Illumination	0.01Lux (0Lux IR on)
Bit Rate	32Kbps~6Mbps
Day/Night	IR-CUT Auto Switch Filter
S/N Ratio	≥52dB
Digital Noise Reduction	3D Digital Noise Reduction
Fast Configuration	Acoustic smart link configuration (WIFI fast configuration)
Motion Detection	Support 4 areas, 0~100 sensitivity
Human Detection	Support 4 areas, 0~100 sensitivity
Support System	IOS, Android, Windows PC client remote view
General Function	Capture, Recording, Motion detection, Alarm, Password protection, Video playback, Remote control, One Button Guarding, Browser view, Administrator and guest setting, etc.
Lens	
Focus Length	3.6mm Lens
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
LED	Dual Light: 2pcs Array IR LEDs+2pcs White Lights
IR Status	Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Protocols	TCP/IP, UDP/IP, HTTP, ICMP, FTP, Email, Telnet etc.
Onvif	Support Onvif 2.4
P2P	Yes
POE	/
Dual Stream	Support
IE Brower	Built-in Web Server, user can directly use browser to view or control
Smart Phone	iPhone, iPad, Android, Android Pad
Wireless	
WiFi	Wi-Fi(IEEE802.11b/g/n),2.4Ghz
WiFi Range	No obstacles 300m Max.
Interface	
SD Card Slot	Support Micro TF Card Slot (Max to 128GB)
Audio	Support two-way audio
Housing	ABS
Operation Temperature	(- 20°C ~ + 60°C_RH95%_Max)
Storage Temperature	(- 20°C ~ + 60°C_RH95%_Max)
Power Supply	DC12V±10%, 2000mA, 1.8W
Dimension	70mm(L)*70mm(W)*108(H)
Weight	500g