

R7-20X

- 1)Configure device through wired/wireless network
- 2)Support PT control: horizontal: 355°, vertical: 110°
- 3)Support Android/iOS/Windows PC client remote view
- 4)Support P2P
- 5)Support latest ONVIF protocol
- 6)2.0 Mega pixels 1/3" CMOS sensor
- 7)3.6mm lens, with IR cut function
- 8)6pcs of LED lights, 10m IR distance
- 9)Fast configuration: acoustic smart link configuration (WiFi fast configuration)
- 10)Support motion detection and human detection
- 11)Built-in MIC and speaker, support two-way audio
- 12)Support TF card, Max. 128GB



WiFi Camera Specification	
Camera	
Image Sensor	1/3" CMOS Sensor
Resolution	2.0MP 1080P
Video Compression Format	H.265
Frame Rate	12fps (PAL/NTSC)
Electric Shutter	Auto
Minimum Illumination	0.01Lux (0Lux IR on)
Bit Rate	32Kbps~6Mbps
Day/Night	IR-CUT Auto Switch Filter
S/N Ratio	≥52dB
Digital Noise Reduction	3D Digital Noise Reduction
Fast Configuration	Acoustic smart link configuration (WIFI fast configuration)
Human Detection	Support 4 areas, 0~100 sensitivity
Support System	IOS, Android, Windows PC client remote view
General Function	Capture, Recording, Motion detection, Alarm, Password protection, Video playback, Remote control, One Button Guarding, Browser view, Administrator and guest setting, etc.
Pan & Tilt	Horizon:355° Vertical:110°
Lens	
Focus Length	3.6mm Lens
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
LED	6pcs Infrared LED, IR distance up to 10m
IR Status	Auto Control
Network	
Ethernet	No RJ-45 (10/100Base-T)
Network Protocols	TCP/IP, UDP/IP, HTTP, ICMP, FTP, Email, Telnet etc.
Onvif	No
P2P	Yes
POE	/
Dual Stream	Support
IE Brower	Built-in Web Server, user can directly use browser to view or control
Smart Phone	iPhone, iPad, Android, Android Pad
Wireless	
WiFi	Wi-Fi(IEEE802.11b/g/n),2.4Ghz
WiFi Range	No obstacles 300m Max.
Interface	
SD Card Slot	Support Micro TF Card Slot (Max to 128GB)
Audio	Support two-way audio
Housing	ABS
Operation Temperature	(- 20°C ~ + 60°C_RH95%_Max)
Storage Temperature	(- 20°C ~ + 60°C_RH95%_Max)
Power Supply	DC12V±10%, 2000mA, 1.8W
Dimension	70mm(L)*70mm(W)*108(H)
Weight	300g