

Model:

C501HDM2A-WL

- 1) Include 3.6mm lens
- 2) 6pcs of warm white LED, IR distance 20-25m
- 3) With cable shield 3-Axis bracket
- 4) Effective pixels: 1920*1080
- 5) UTC control, 4in1 AHD/CVI/TVI/CVBS can be adjusted on DVR's coaxial control menu, can adjust image & functions freely
- 6) Transmitting distance up to 500M



Specification	C501HDM2A-WL
Camera	
Image Sensor	1/2.9" CMOS, IMX323
Image Resolution	P: 25fps@1920(H)*1080(V) N: 30fps@1920(H)*1080(V)
Minimum Illumination	Color: 0.01Lux @ (F1.2,AGC ON),0 Lux with IR B&W: 0.001Lux@ (F1.2, AGC ON), 0Lux with IR
Electric Shutter	1/25s~1/50,000s, 1/30s~1/60,000s
TV System	PAL/NTSC
Sync System	Internal
S/N Ratio	≥50dB
Video Output	AHD/TVI/CVI/CVBS (960H) (BNC)
Lens	3.6mm lens
IR Distance	6pcs of warm light LED, IR distance 20-25m
IR Power On	No
D&N Mode	Full Color
OSD	Support
OSD Menu Language	EN, CN
DNR	3D NR
Picture Adjustment	Yes
White Balance	Auto/Manual
Gain Control	Auto
Vandal-proof Housing	Metal
Power Input	DC12V±10%
waterproof Rate	IP 66
Operation Temperature	Temperature -10°C~+50°C, Humidity less than 95%RH
Storage Temperature	Temperature -20°C~+60°C, Humidity less than 95%RH
Dimension	150mm(L) * 82mm(W) * 75.1mm (H), not including size of bracket 201mm(L) * 82mm(W) * 75.1mm (H), including size of bracket
Weight	550g